

# SPECIAL WASTE CONTAINER TYPE SAP-1



For the international transport of solids and paste-like substances according to ADR/RID and the IMDG code, packing groups I, II and III

- IBC according to DIN standard 30741, part 1
- construction made of 2 mm steel sheet, lid and base frame 2.5 mm steel sheet
- reinforced edging
- full-length fork sleeves
- sturdy stacking corners with crane lifting eyes
- suitable for pick-up by a pallet truck, forklift or crane
- spring-loaded lid with a seal
- 2 lid fasteners, lockable
- automatic lid lock in 270° position
- lid support in 70° position
- max. density 1.5 kg/l
- finish hot-dip galvanized or with additional painted finish (outside only)

### Accessories

- PE foil bags (100 bags/roll)
  - PE inlay
  - embossed company name
  - dual code
- NB Please remember to check whether this option is regulation compliant for you! (A dual code is permitted in Germany)



SAP 800-1 with dual code (Please see Accessories)



SAP 800-3 with 2 lid fasteners (1 lockable)

### UN-APPROVALS

- 11A/X/D/BAM 6007-BAUER/4960/
- 4A/X/S/D/BAM 6917-BAUER

	Volume in l	Dimensions in mm (l x w x h)	Can be stacked	Total permitted weight in kg	Weight in kg
SAP 450-1	450	1200 x 1000 x 835	3 high	825	155
SAP 600-1	640	1200 x 1000 x 1053	3 high	1124	164
SAP 800-1	800	1200 x 1000 x 1235	3 high	1375	175
SAP 800-3	800	1200 x 1000 x 1235	3 high	1375	175

Finish:

hot-dip galvanized