

Husmann®

Umwelt-Technik



Portable compactor suitable for bulky waste

The portable Husmann compactor model SPB-SM has been designed especially for the heavy duty demands existing when bulky waste is compacted, for instance on recycling plants.

In addition to the outstanding features of the portable compactors of the E-generation the advantages of this machine are an extremely solid design achieved through thicker steel plates and special accessories which proved to be successful for compacting bulky waste.

Thanks to additional accessories every compactor can be adapted to the special demands of its place of installation.

Husmann®
Umwelt-Technik

QUALITÄTS-
MANAGEMENT
Wir sind zertifiziert
Regelmäßige freiwillige
Überwachung nach ISO 9001



D-26892 Dörpen

Am Bahnhof
Tel. 0 49 63/9110-0
Fax 0 49 63/9110-50

www.husmann.com

D-49762 Lathen

Gerhard-Husmann-Str. 4
Tel. 0 59 33/93 18-0
Fax 0 59 33/9318-50

D-74564 Crailsheim

Roßfelder Straße 55
Tel. 0 79 51/93 79-0
Fax 0 79 51/93 79-29

e-mail: info@husmann.com

D-16909 Wittstock

Gewerbepark
Tel. 03 39 62/60 01-0
Fax 03 39 62/60 01-2

Technical Specification

MODEL	SPB SM 18 SEL	SPB SM 20 SEL	SPB SM 22 SEL		
Capacity (m ³)	18	20	22	Power	5.5 kW
Length (mm)	6.360	6.760	7.160	Compaction force	340 kN
Width (mm)	2.550	2.550	2.550	Volume per stroke	1.7 m ³
Height (mm)	2.580	2.580	2.580	Volume per hour	theor. 104 m ³
				Cycle time	59 s
				Penetration depth	420 mm
				Fill.opening (top)	1.860 x 1.860 mm
				Fill.opening (bottom)	1.500 x 1.860 mm
				Filling height	1.520 mm



reinforced ram



option: hydraulic retaining door

Quality features of the portable compactor for bulky waste

- ❖ two vertical sections in the container wall towards the compactor
- ❖ complete container made of 4 mm steel sheet
- ❖ additional horizontal steel sections in the header bar area
- ❖ sealed inspection hatches
- ❖ compactor floor made of highly wear and tear resistant 10 mm steel plate
- ❖ low-noise power pack
- ❖ covering plate of hydraulics reinforced
- ❖ reinforced guide plates
- ❖ tiltable hook on the filling side
- ❖ temperature and float switch
- ❖ container floor made of highly wear and tear resistant 5 mm steel plate, reinforced with several cross members
- ❖ pendulum steel scraper fitted to the bottom of the ram face
- ❖ ram cuts out in the retracted position, which means that the charge box is open on starting work
- ❖ rigidly welded retaining pins of sturdy design at the header bar
- ❖ ratchet door locking mechanism
- ❖ ram in reinforced design

We offer extensive service: own rent and leasing company, reliable after-sales service, modern engineering department

Portable compactors - static compactors - transfer stations - large volume containers - skips - shredding systems - file shredders - special constructions

The machines shown are equipped with accessories which are not included in the base price.